

NTI e-ipcam-dhnp0-p 1/2.8 inch CMOS High-Definition Wired Day/Night Outdoor IP Dome Camera with PoE/F2.0/2.8 mm Fixed Lens

1/2.8" CMOS High-Definition Wired Day/Night Outdoor IP Dome Camera with Power over Ethernet (PoE), Lens: F2.0; 2.8 mm fixed

Features:

- View the camera from the ENVIROMUX web interface, camera web interface, included software, or with a compatible cell phone.
 - Control the camera using the camera web interface accessible from the ENVIROMUX web interface.
- With the E-2D/5D/16D, a triggered snapshot can be forwarded in alert e-mails or stored locally on a connected flash drive.
 - A snapshot can be triggered by any programmed event (motion detection, door open/close, glass break, smoke, liquid detection, etc.)
- 1/2.8" Progressive Scan CMOS
- Video Compression: H.264/MJPEG/H.264+
 - Supports simultaneous dual streaming
- Audio Compression: G.711/G.722.1/G.726/MP2L2
- 2MP resolution @ 30 fps
 - Supports 1920x1080, 1280x960, 1280x720
- Night Vision IR Range: 98 feet (30 m)
- Lens: F2.0; 2.8 mm fixed
 - Angle of View: 106° (2.8 mm)
- Power:
 - Input: 100 to 240 VAC at 50 or 60 Hz
 - Output: 12 VDC, 1A external power adapter (included)
 - Max consumption: 5 W
 - Power over Ethernet standards supported: IEEE 802.3af
- 10/100 Mbps Ethernet port for wired connections.
- Micro SD memory card slot (up to 128G GB)
- System compatibility: ONVIF, PSIA, CGI, ISAPI
- Operating temperature: -22 to 140°F (-30 to 60°C).
- Dimensions WxH: 4.4x3.2" (111x82 mm)
- Waterproof rating: IP67
- Compatible with E-2D/5D/16D.
- Regulatory approvals: FCC, UL, RoHS