

SECO-LARM SK-1123-FDQ Vandal Resistant Flush-Mount Access Control Keypad

Vandal Resistant Flush-Mount Access Control Keypad

Features

- 12~24 VAC/VDC auto-adjusting operation
- Up to 1,000 possible user codes (000~999) programmable for output 1 and 100 (001~100) for output 2
- Up to 50 (01~50) possible temporary visitor codes, which can be programmed for one-time or limited-time use (1~99 hours)
- Output 1: Form C relay, 1A@30VDC max.
- Output 2: Transistor ground, 100mA@24VDC
- Outputs 1 and 2 can be programmed to activate for up to 99,999 seconds (nearly 28 hours)
- Tamper output: N.C. Dry contact, 50mA@24VDC max
- Mounts to standard single-gang back box
- IP66 Weatherproof rating
- Keypad illuminates when a button is pressed; backlight can be programmed for FULL or AUTO in standby mode
- All features are programmed directly from the keypad: No need for an external programmer
- EEPROM Memory protects programmed information in case of power loss
- Up to 50 (01~50) duress codes for output 1, 10 (01~10) for output 2
- Duress code signals a silent alarm if an authorized user is forced to open the door under duress
- Egress input lets users exit the premises without keying in the code
- Door sensor input for anti-tailgating operation
- Interlocking input for connecting to a second keypad