

SECO-LARM SK-1123-SPQ Vandal Resistant Outdoor Access Control Keypad with Proximity Reader

Vandal Resistant Outdoor Access Control Keypad with Proximity Reader

Features

- Built-in proximity reader. 125kHz (EM125)
- 4 Available programmable access modes for all 3 outputs: card only, code only, card and common user code, card and unique user code
- 1,100 Users over 2 Outputs. Codes may be 4~8 digits: - Output 1 – Form C relay, 1A@30VDC, 1,000 users - Output 2 – Form C relay, 1A@30VDC, 100 users
- Outputs can be programmed to activate for up to 99,999 seconds (nearly 28 hours)
- Super user code gives admin access to keypad
- Up to 50 (01~50) possible temporary visitor codes, which can be programmed for one-time or limited-time use (1~99 hours)
- Programmable egress input with optional warning alarm and delayed egress
- Real-time clock to auto-disable access at specific times
- Up to 50 (01~50) duress codes for output 1 and 10 (01~10) for output 2
- Duress code signals a silent alarm if an authorized user is forced to open the door under duress
- 12~24 VDC/VAC Auto-adjusting operation
- All features are programmed directly from the keypad: No need for an external programmer
- IP66 Weatherproof rating
- Mounts to a standard single-gang back box (surface-mount back box included)
- Durable and attractive stainless steel faceplate
- Tamper output: N.C. Dry contact, 50mA@24VDC max.
- Keypad illuminates when a button is pressed; backlight can be programmed for FULL, AUTO, or OFF in standby mode
- Mantrap: for a protected area with two doors, this feature allows only one door to be open at a time
- Door sensor input for anti-tailgating operation
- Door-propped-open warning
- Door-forced-open warning
- EEPROM Memory protects programmed information in case of power loss