

## Gefen EXT-WHD-1080P-LR-b Wireless HDMI Extender (Receiver/Sender) Kit with IR upto 100ft

The Wireless for HDMI 5 GHz LR (Long Range) Extender system sends high definition audio and video to any HDTV display up to 100 feet (30 meters). It extends HDCP-compliant HDMI AV content from computers, game consoles, set-top boxes, Blu-ray players, and other AV sources to a remotely located display. HD resolutions up to 1080p Full HD, 7.1 channels of LPCM digital audio, and 5.1 channels of Dolby® or DTS® formats are supported. This wireless system is comprised of a Sender and a Receiver unit. Both units can be attached to a standard ¼"-20 camera tripod mount, wall mounted, or be placed on a shelf. The small and low-profile Receiver unit includes a wired IR Extender module, and can be hidden away behind the display or inside an equipment cabinet if needed. The Sender features two HDMI inputs and an HDMI output for connection to a local display. The end-user can select between the two HDMI sources by using the included handheld IR remote or by pressing the Input button on the Sender or the Receiver unit. The included IR emitter array can be connected to the Sender unit and attached to the IR sensor windows of the two Hi-Def sources, allowing full control of the source unit from another room simply by pointing the IR remote of the source at the Receiver unit. This wireless extender system is ideal for high-definition AV extension in a conference room, classroom, auditorium, home theater, and multiform AV installations that feature multiple sources and two displays. Up to eight Sender units can be accessed by a Receiver, one at a time, using its handheld remote control. The Wireless for HDMI 5 GHz LR Extender system can transmit through walls and does not require line-of-sight placement of its transceivers.

### Features

- Wireless extension of HDMI up to 100 feet (30 meters) \*\*
- Supports resolutions up to 1080p Full HD, up to 7.1 channels of LPCM digital audio, and up to 5.1 channels of Dolby® and DTS® format
- Transmits through obstacles – does not require line-of-sight
- Long Range performance makes it ideal for multi-room use
- IR Back Channel for source control with carrier frequency selector
- Uncompressed High Definition A/V from source to display
  
- Less than 1 frame latency
- AES 128 Encryption
- Compatible with legacy DVI displays
- Handheld IR remote for easy setup and operation
- Firmware update via Mini-USB port using Gefen Syner-G™ software
- WHDI 1.0, FCC Part 15, IC, and ETSI-compliant

### HDMI Features Supported

- CEC
- 12-bit Deep Color
- 3DTV pass-through
- HDCP pass-through
- Lip Syn

### Sender unit:

- 2 HDMI Inputs
- Local HDMI “Mirrored” Output
- IR Output port and included Emitter Array for source control
- Ideal for use with 2 sources in a fixed home theater type installation
- Flexible mounting options: ¼"-20 thread, wall mounting, shelf placement

### Receiver unit:

- IR Extender module included for hidden installations
- Small and compact form factor – can be installed behind the TV
- Flexible mounting options: ¼"-20 thread, wall mounting, shelf placement