

Kramer T-1GD Mounting Bracket for Installing 1-Gang US-D Size Product Inside TBUS

T-1GD is a bracket for installing a Kramer 1-Gang US-D size wall plate in a TBUS. It fits into a dual power socket opening of the TBUS inner frame.

Features

- High Performance Extender — Professional DGKat™ 2.0 extender kit for providing long-reach signals and 2-way power over twisted pair copper infrastructures. PT-871/2xr-Kit extender employs low-level video compression technology that delivers visually lossless performance for 4K@60Hz (4:4:4) HDR signals with near-zero latency. PT-871xr converts the HDMI input signal into the transmitted DGKat™ 2.0 signal. PT-872xr converts the transmitted DGKat™ 2.0 signal into an HDMI signal. PT-871/2xr-KIT extends video signals to up to 60m (200ft) at 4K@60Hz (4:4:4) resolution and up to 70m (230ft) at 4K@60Hz (4:2:0) 24bpp resolution over Kramer shielded cables.
- HDMI Signal Extension — HDR, HDMI 2.0 and HDCP 2.2 compliant. Supports deep color, x.v.Color™, lip sync, HDMI uncompressed audio channels, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D. EDID signals are passed through from the source to the display.
- I-EDIDPro™ Kramer Intelligent EDID Processing™ — Intelligent EDID handling, processing and pass-through algorithm that ensures Plug and Play operation for HDMI source and display systems.
- Multi-channel Audio Extension — Up to 32 channels of digital stereo uncompressed signals for supporting studio-grade surround sound.
- Cost-effective Maintenance — Status LED indicators for HDMI and DGKat™ 2.0 ports facilitate easy local maintenance and troubleshooting.
- Easy Installation — Single twisted-pair cable for signal and power wiring. Compact Pico TOOLS™ fan-less enclosure for device-back mounting, or side-by-side mounting of 4 units in a 1U rack space with the optional RK-4PT rack adapter.

APPLICATIONS

- Long-distance AV signal extension for large room connectivity
- AV extension in meeting rooms, boardrooms, hotels and corporate facilities