

Electro-Voice SX600PIX Sx Series Dual 12 inch 2-Way 70V 600W RMS/2400W Peak Speaker (Black/Weatherized)

This listing is for SX600PIX Speaker only. Use description below as a general reference.

The Electro-Voice Sx600PI and Sx600PIX are higher power extensions of the popular Sx-series of weather-resistant indoor/outdoor speaker systems. The Sx600 series features a dual 12 inch, Two-element vertical array based on the powerful Neodymium woofer developed for X-Array. Mid-bass and low frequency energy is augmented by an overlapping DL series woofer to produce vertical pattern control and intelligibility superior to conventional horn systems. The HF section features the DH2t compression driver coupled to a molded-in 65° x 65° Constant Directivity horn using EV's unique Varipath throat geometry. An EV exclusive SuperSAM mounting system allows 60° of vertical adjustment and 180° of horizontal pan with simple adjustment. The molded polymer enclosure combined with aluminium and neodymium components provide a lightweight, easy to handle system. A multilayer stainless steel grille protects against rain, sprayed water, and dust to IEC 529 IP 44 Mil Spec 810 humidity, salt spray, and UV specifications.

The Sx600PIX features a special internally mounted 600 Watt line transformer for operation on 70, 100, 140 and 200 volt distributed line systems. The Sx600 series is ideally suited for applications requiring high intelligibility sound at high SPL's in applications such as arenas, stadiums and race tracks.

Features:

- Very High Sensitivity, 105 dB 1 W/1 m (139 dB Peak SPL)
- Easy, Versatile, SuperSAM Mounting System included
- All Weather IEC 529 IP 44 & Mil Spec 810 Environmental Specs
- Available 600 Watt Internal Transformer (Sx600PIX)
- EN54-24 Type B certification 1438-CPD-0300
- Waterproof connection by SJO cable with gland nut