

## Apantac UE-4-K 4 input 4K/UHD HDMI multiviewer with KVM functions

4 input 4K/UHD HDMI multiviewer with KVM functions. Accepts 4 HDMI 2.0 inputs with HDCP Support, 4 USB inputs, 16 GPI for tally/presets. RS232 for 3rd party interface. 30 internal presets. Supports AXP API. HDMI Output up to 4096x2160@ 50/60Hz and 12G SDI Output. 2 RU.

### Features

- 4 x HDMI 2.0 inputs
- with built-in KVM functions
- 1 x HDMI 2.0 output, 1 x 12G output
- Windows can be sized and moved freely
- Decode up to 8 embedded audio per HDMI input
- Total of 32 audio meters
- 2 simultaneous and identical HDMI 2.0 and 12G SDI outputs
- Multiple units can be cascaded together to expand the I/O
- Ethernet for configuration and external control
- Dynamic UMD/labels & Tallies (TSL)
- Stand alone labels, 2 customizable logos
- 16 GPIs for tallies, count up/down triggers or preset recall
- 1 digital and 1 analog clocks can be sync'd with LTC or NTP
- Borders can be turned on or off
- Two sets of safe area markers
- Visual Alarm tags for video/audio alarm detection
- Audio monitoring output - Stereo, AES, Embedded SDI and HDMI
- 2 Rack Units
- Redundant power supply
- 3 year limited warranty

### Accessories

- Rack mount
- 2 x RJ45 to DB9 for GPI
- 2 x breakout terminal blocks
- RJ45 to DB9 for serial