

Electro-Voice X2212/90 High-Performance Compact 12 inch 90deg Vertical Line Array Loudspeaker System

The X2-212/90 from Electro-Voice is a two-way vertical line array loudspeaker can be used in a wide variety of applications where wide bandwidth, vertical and horizontal directivity control, and high efficiency are required in a compact cost-effective package. For high frequencies, the X2-212/90 utilizes two (2) ND6A high-output large format 3-inch titanium compression drivers directly coupled to a pair of PDH Plane Wave Generators on a 90° waveguide optimized for uniform pattern control and smooth, linear response. For low frequencies, the DVN3125 12-inch neodymium woofer was developed using Finite Element Analysis to optimize motor, suspension, and electrical design for very low distortion, high efficiency, and maximum intelligibility at high SPL. The MBH effectively emulates the acoustic behavior of a double line of four (4) 3-inch point sources to deliver superior mid-band coupling while maintaining the efficiency, power, and bandwidth of a 12-inch transducer. The Bi-amp only X2-212/90 requires proprietary Electro-Voice FIR-Drive.

Electro-Voice FIR-Drive is the combination of brick wall crossovers, phase correction, FIR EQ, peak anticipation limiter and Thermal Limiter. These technologies yield superior, nearly inaudible transducer protection with linear summation, smooth off-axis response, and unparalleled acoustical performance over the critical vocal and instrument range regardless of array size.

The X2-212/90 is a premium solution for demanding live sound reinforcement and fixed-install applications. The vertical trapezoidal enclosure is constructed of weather-resistant birch and coated with EVCoat for enhanced durability. The enclosure features the IRS, a captive twist-lock multi-angle arraying system designed by Electro-Voice to significantly reduce loadin/load-out time of any size array. IRS has been engineered with the flexibility to deploy a system using the two (2) most common methods of array set-up:

- Compression method by using a pull-up kit (Sold separately).
- Fixed angles locked by using secondary rigging pins (Included).

X2-212/90 with IRS rigging is rated for use for up to 24 elements for normal arrays. LAPS 3 or higher (Line Array Prediction Software) accurately provides fast array configuration for coverage results, rigging details and allowed rigging configurations. It also provides information for the creation of steered/shaped subwoofer arrays.

The input panel provides dual Neutrik NL8 connectors for fast connectivity between loudspeakers. X2-212/90 is Bi-amp operation only. The advanced acoustic and mechanical designs of X2 series loudspeakers, combined with LAPS 3, provide the tools and flexibility to easily design and deploy high performance vertical line array systems.

Features:

- DVN3125 12-Inch Neodymium Woofer
- Higher Output, Lower Distortion
- Mid-Band Hydra (MBH) Superior Box Coupling
- Advanced PDH Pin Diffraction Hydra Controlled Linear HF Performance
- Integrated Rigging System (IRS) Quick Setup