

Lab.gruppen C 88:4 230E 8800W 4-Ch Amplifier w NomadLink Network Monitoring/Dedicated Control for Install Applications/230E

This listing is for C 88:4 230E Amplifier only. Use description below as a general reference.

C SERIES C 88:4 230E

The C 88:4 is the new flagship of the C Series and is the most powerful single frame, 4-channel installation amplifier ever built! Delivering an amazing 4 × 2200 W at 4 ohms, this amplifier is powerful enough for the most demanding of installed sound applications including, larger sub-woofers, large array systems and broader multi-power-level/impedance applications. Packaged in a compact 2U chassis, the C 88:4 sets a new benchmark for extreme power and flexibility in an installation-dedicated amplifier.

C Series amplifiers are uniquely capable of adapting to a wide variety of demanding load conditions. Each channel has an individually configurable Voltage Peak Limiter (VPL™), which allows the output to be optimized for any loudspeaker load - whether one massive subwoofer or a series of small 100/70 V loudspeakers. VPL works in combination with adjustable input gain to achieve maximum headroom regardless of input levels or output impedances.

Features:

- 8,800 Watt, 4-channel amplifier with up to 2,200 Watts output per channel and NomadLink network for monitoring and control
- Selectable gain plus scalable Voltage Peak Limiter (VPL) and bridge-mode operation allow custom configuration for any application
- 4 x 2,200 Watts into 4 Ohms, 230V US
- Proven and reliable Class-TD output stage delivers Class-A/B audio quality with Class-D efficiency
- Regulated Switch Mode Power Supply (R.SMPS) ensures constant power output at all times
- Intuitive DeviceControl software monitors and controls key functions via the NomadLink network
- Comprehensive protection scheme including current, voltage, DC, temperature, short circuit and open load warnings
- Efficient Intercooler copper cooling system dissipates more heat for extended peak output
- 4 x balanced analog audio inputs on 3-pin Phoenix* connectors
- 4 x barrier strip 2-pole screw terminal output connectors
- Removable dust filter grille for increased air circulation
- Compact and durable 2U rackmount chassis saves space in install applications
- 10-Year Warranty Program*
- Designed and engineered in Sweden