

Datavideo TLM-102 Dual 10 inch Monitor

The TLM-102, Dual 10.1" 4RU Rack mount monitor, is a broadcast quality monitoring system with built-in vectorscope/waveform monitor and video signal converters. Each monitor has one SDI input and one HDMI input. Each monitor also has one SDI output and one HDMI output. Built-in signal conversion allows each monitor to use one input for monitor display and the other input for signal conversion. The same can be done simultaneously with monitor 2.

The 4RU rack mount design offers various of mounting methods for on-site monitoring, video wall and video production vans. Excellent display with advanced auxiliary functions also provides viewing & friendly user experience.

TLM-102 pairs perfectly with the SE-500HD Video Switcher for multi-view monitoring on the left side and program output monitoring on the right (or vice-versa).

Features:

- 1280*800 IPS Panel resolution
- Dual monitor, 4RU rack mount
- Support 3G-SDI video input with loop-through output
- Support HDMI input with loop-through output
- Support column (YRGB peak), time code, waveform, vector scope & audio level meter, peaking, zoom, pix to pix, underscan, check field, etc
- SDI, HDMI cross conversion
- Individual adjustments of Brightness, Contrast, Color Saturation and LED
- Backlight Level for each monitor
- Color temperature for user to select
- Front panel headphone jacks
- User-definable function buttons F1, F2