Aurora Multimedia HTW-2-W 4K60 HDR 1xVGA/2xHDMI input HDBaseT 2.0 Wall Plate Extender (Transmitter) up to 100m/330ft (White)

This listing is for HTW-2-W only. Use description below as a general reference.

The HTW-2 HDBaseT 2.0 transmitter wall plate is part of Aurora's HT Series capable extending 4K60 4:4:4 & HDR (18Gbps) 100m (330') with unshielded cable. This 2 gang low depth Decora™ wall plate is not only stylish but extremely functional with 3 inputs (1 VGA & 2 HDMI). Directional USB to allow a user to choose which side the host (PC) vs the device (peripheral) will be located. Built in IP port expansion allows any 3rd party control system to send commands directly to the unit for source switching, RS-232, and IR control. Aurora is the only product to allow a single PoE port power both the TX and RX at the same time with no wall supplies required for a very clean installation. For easier integration into an audio system, the HT Series is the only HDBaseT product to have optional Dante/AES67 up to 8 channels for surround sound. The Aurora HT Series re-invents the capabilities of HDBaseT beyond the typical point to point making it the ultimate HDBaseT integrator solution.

Features:

- 4K60 4:4:4 HDR 18Gbps
- 100m (330ft) with Unshielded Cable
- HDMI® 2.0/HDCP 2.2
- Audio DSP & Dante[™]/AES67 Options 2 or 8 Channel
- Operate & Power both TX & RX from a PoE Switch
- Auto Switching
- Two HDMI® Inputs & One VGA Input
- 10/100 LAN Ports
- USB 2.0 Device/Host with Selectable Direction
- IP, RS-232 & IR Control