

Hikvision DS-7208HQI-K2/P + DS-2CE56H5T-IT3E 8CH TurboHD DVR with 8x 5MP PoC Turret Cameras and HDD 6TB Kit

DS-7208HQI-K2/P

TurboHD DS-72xxHQI-Kx and DS-72xxHQI-Kx/P Series DVRs feature a range of self-adaptive signal inputs and offer camera support on up to 16 channels. They offer transmission distances of up to 2,630 ft (800m) on 1080p, and 3,940 ft (1,200m) on 720p HD-TVI.

Features

- Analog Video Input 8-ch
- H.265+ / H.265 / H.264+ / H.264 and Dual-Stream Video Compression
- Full Channel Recording at up to 2 MP
- Main stream: When 1080p Lite mode not enabled: For 3 MP stream access: 3 MP / 1080p / 720p / VGA / WD1 / 4CIF / CIF @ 15 fps
- HDMI and VGA Output up to 3840 x 2160
- Up to 16-ch Synchronous Playback Support

DS-2CE56H5T-IT3E

5 MP Outdoor Ultra-Low Light PoC Turret Camera

The Hikvision DS-2CE56H5T-IT3E 5 MP Outdoor Ultra-Low Light Power-over-Coax (PoC) Turret Camera provides high definition analog output. TurboHD means that the analog signal can be sent over existing coaxial cable, eliminating the need to run new cables for high definition video.

Features

- Minimum Illumination: Color: 0.008 Lux @ (F1.2, AGC ON), 0 Lux with IR
- Up to 2560 x 1944 Resolution
- 2.8 mm, 3.6 mm, 6 mm, 8 mm, or 12 mm Fixed Focal Lens
- Frame rate: 2560 x 1944 @ 20 fps, 2560 x 1944 @ 12.5 fps; 2560x 1440 @ 30 fps, 2560x 1440 @ 25 fps (default); 1920x1080 @ 30 fps, 1920x1080 @ 25 fps *2560 x 1944 @ 12.5 fps is not available in PoC mode.
- EXIR 2.0 with up to 130 ft (40 m) IR Range
- 12 VDC \pm 25% / PoC.af