

OWI AMP-CAT602-1B- One Surface Mount Amplified Speaker/Black

2-Way, 6.5" Woofer, Versatile, Low Voltage, Self-Amplified, Surface Mount Speaker featuring an Aluminum Grill, Hill-Impact Polystyrene Housing and Mounting Bracket. Perfect for Schools, Hotels, Conference Rooms and Training Rooms. Low Voltage Amplified surface mount speaker combination. Each powered speaker. CAT5 connection integrates quickly with OWI devices like volume control, Bluetooth volume and MC4 mini mixers. Can daisy chain one additional AMP-CAT speaker from CAT5 connection. Power can be sent or received via the CAT5 cabling. Comes with 15VDC Level V power supply model PS15VDC35AL5 for localized power.

Connects with:

- AMP-BTVC
- AMPSTVCW
- MC4
- MC4-D
- MC4-BT

Features:

- 2- way, 6" woofer
- 15VDC Level V power supply and mounting bracket included
- 2 Line Level Input/Sources
- Up to 20 Watts of Power - right at the speaker
- CAT5 input and output for connection with OWI AMP and devices
- With a 3.5 mm Stereo Jack Line Input
- Lower Noise Feature
- Perfect for schools, hotels, conference rooms and training rooms
- Color: Black