

TVLogic LVM-212W 21.5 inch Component/3G-SDI/DVI/HDMI Full HD 1920x1200 LCD Monitor

LVM-212W is an ideal rack-mount monitor for video wall in control rooms and OB Vans. Inside the beautiful slim bezel design that just fits into a 19" rack, integrated the wide viewing angle LCD panel with native Full HD resolution and 16.7M colors and TVLogic's unique video processing technology that enables high picture quality 3G-SDI and all the professional features.

Features

- **Compatible with various SDI signals formats (SD/HD/3G)**
 - This product is compatible with various SDI signals - SD/HD/3G(A/B)- SDI 480i,576i,720p,1080i/p,1080psf
- **Compatible with various Analog signals**
 - This product is compatible with various analog signals such as CVBS(Composite), S-Video, YPbPr(Component) and RGB.
- **HDMI/ DVI Digital(HDCP)/ DVI Analog function built-in**
 - HDMI, DVI Digital(HDCP) and DVI Analog(VGA) Inputs are available without any additional accessory.
- **All-in-one type system**
 - Slim and all-in-one type monitor that requires no other accessory, for optimized space utilization.
- **Waveform/Vectorscope/Audio Level Meter Function**
 - Waveform & Vectorscope.
 - Embedded Audio Level Meter.
- **Luma(Y') zone check(Color/Zebra type)/ Range error Function**
- **Audio in & out**
 - Internal Speaker(activates only with input signals with Embedded Audio)
 - Stereo Audio Out & External Audio In through phone Jack.
- **BLUE ONLY/MONO/Focus-Assist/H/V delay**
- **Internal pattern generator(0~100% Gray/ Colorbar+Pluge)**
- **Various Markers & Safety Areas**
 - Center Marker, Safety Area Marker, Aspect Marker, Display Size(Scan)
- **Knob Control**
 - Easy to adjust user configuration using the control Knob on the front of the monitor.
- **1:1 SCAN / Zoom**
 - 1:1 SCAN : Used to display the original image resolution without scaling to match a certain resolution or an aspect ratio.
 - Zoom: Used to enlarge the original image.
 - Zoom Scroll Function (Left/Right, Top/ Bottom)
- **Wide screen compatible**
 - Native 16:9 Wide Screen
- **External control function**
 - This product can be controlled by using parallel switch, RS-422 and Network simply with cable connection without additional peripheral equipment attached to the unit
- **RS422/UMD feature support**
 - This product supports protocols provided by TVLogic or a TSL protocol.
- **AC/DC Compatible**
 - Basically, this product is powered by normal AC power source and can also be powered by DC 24V as well.
- **Additional Features**
 - Wide Viewing Angle, Loop Through (SDI/ Analog), VESA Mounting Standard, Contrast Ratio of 1000:1, Luminance of 365 cd/m2 OSD user interface and Rack Mountable.