

Atlona AT-HDSDI-AV Atlona HD-SD/SDI to HDMI-DVI-YPbPr-Composite-RGBHV Converter

Atlona AT-HDSDI-AV HD-SD/SDI to HDMI-DVI-YPbPr-Composite-RGBHV Converter Model: AT-HDSDI-AV

Atlona AT-HDSDI-AV provides high quality 12 bit conversion between SDI digital video input and HDMI / DVI digital video output or YPbPr / Composite (CVBS) / RGBHV analog video output. Plus, with an extra DVI output through HDMI type A connector, users can have pure digital video transmission path without analog conversion distortion. The AT-HDSDI-AV supports both SD-SDI and HD-SDI formats (SMPTE 259M, SMPTE 292M, and SMPTE 296M), and also features 2 equalized SDI loop outs.

Features:

- Excellent quality 12-bit D/A conversion
- Supported high-definition (HD) formats:
1080i @50/59.94/60Hz, 1035i @50/59.94/60Hz, 720p @50/59.94/60Hz
- Supported standard-definition (SD) formats:
NTSC @59.94Hz, PAL @50Hz
- Default SDI / YPbPr / DVI Patterns
- Auto HD/SD-SDI detection
- 2 Equalized loop outputs
- Easy installation
- SD outputs: HDMI (video only) / DVI / YPbPr
- HD outputs: HDMI (video only) / DVI / YPbPr / RGBHV
- External DIP Switch Configuration

Specifications:

- Video Bandwidth: 270 Mbps/1.485 Gbps, 1.485/1.001Gbps
- Input signal: HD/SD-SDI (SMPTE 259M / SMPTE 292M / SMPTE 296M)
- Output signal: HDMI (video only) / DVI / YPbPr / RGBHV
- Input transmission range: up to 150m / 500ft at HD-SDI or 300m / 1000ft at SD-SDI
- Loop out: 2 equalized SDI outputs
- Power Supply: 5V 4A DC
- Dimensions: 120mm x 110mm x 25mm / 4.7"x4.3"x1" (L x W x H)
- Weight: 420g / 15oz

Package Includes:

- 1x AT-HDSDI-AV
- 1x 5V 4A power adapter
- 1x User Manual
- 1x VGA to YPbPr adapter
- 1x HDMI to DVI adapter

Warranty:

3 year manufacture warranty (parts&labor)