## Atlona AT-VGA0404-A Atlona 4x4 Professional VGA with Audio Matrix Switch

#### Atlona 4x4 Professional VGA with Audio Matrix Switch. Model: AT-VGA0404-A

The Atlona AT-VGA0404-A is an 4 input 4 output Commercial VGA with Audio matrix switcher. The AT-VGA0404-A is one of the world&39;s advanced matrix switchers. Is is capable of being controlled though RS232 via software included or via a third party control system. Switcher is designed to handle any resolution up to UXGA (1600x1200) without any signal degradation. The switcher is capable of routing audio signals in a different matrix then video if applicable.

This device is mainly used in broadcast room, multi council-chamber, television teaching room and command center.

#### Main Features:

- Power-Fail Protection, allows switcher to restore previous settings
- LCD display, shows all programmed commands and switcher responses
- Preset ability, allows user to save specific tasks under one of the 10 presets and call it back with shortcut
- RS232 Communication Control Input, allows to control switcher via included advanced Control software or Third Party Control System
- IR Remote Control
- Audio and Video could have a separate matrix modes (Example: Video in 1 ---> Video Out 2, while Audio in 1---> Audio Out 3)
- Inputs: 4 x VGA female15-pin HD, 4 x 1/8&39;&39; (3.5mm) mini Audio
- Outputs: 4 x VGA female 15-pin HD, 4 x 1/8&39;&39; (3.5mm) mini Audio
- Connectors: 15-pin HD (Could be used for PC resolutions up to UXGA 1600x1200 or HDTV up to 1080p)
- Compatible Formats: RGB, YPrPb or RGBHV
- Lock Safe, allows user to lock unit from being accidentally switched to incorrect mode
- · Undo Function, allows user to undo the incorrect operation and return to the previous setting
- Standard 19&39;&39; Rack Mount Size 1U

#### **Technical Specifications:**

- High Resolution Support: up to 1600x1200@85Hz or even higher
- Bandwidth: 250MHz @ (-3dB), fully loaded @1600x1200@85Hz or higher
- Cross talk sum: 60dB @10M; -39dB @100M
- Switching speed: 200 ns (Max)
- Signal type: RGB, YPrPb, RGBHV, RGBS, RGsB, RsGsBs
- Audio Connectors: 1/8&39;&39; (3.5mm) mini audio
- Standard 19&39;&39; Rack Mount Size 1U
- Temperature: 20C to +70C (-20 F to 158 F)
- Power Supply: 110V-240V (50-60Hz)
- Dimensions (mm): W 485 X H 44.6 X D 242
- Dimensions (inch): W 19 X H 1.71 X D 9.53
- Unit Weight: 1.8kg or 4LB
- Gross Package Weight: 7LB

## **Package Includes:**

- 1 x AT-VGA0404-A
- 1 x RS-232 Communication Cord
- 1 x Power Supply Cord (US)
- 1 x CD with RS232 Application Software
- 1 x IR Remote
- 1 x User&39;s Manual and Quality Guarantee

# **Warranty:**

2 year manufactures warranty (parts and labor)