## Atlona AT-RGB0802 Atlona 8x2 Professional RGBHV Matrix Switch

#### Atlona 8x2 Professional RGBHV Matrix Switch. Model: AT-RGB0802

The Atlona AT-RGB0802 is an 8 input 2 output Commercial RGBHV matrix switcher. The AT-RGB0802 is one of the world&39;s advanced matrix switchers. Is is capable of being controlled though RS232 via software included or via a third party control system. Switcher is designed to handle any resolution up to UXGA (1600x1200) without any signal degradation.

This device is mainly used in broadcast room, multi council-chamber, television teaching room and command center.

#### **Main Features:**

- Power-Fail Protection, allows switcher to restore previous settings
- LCD display, shows all programmed commands and switcher responses
- Preset ability, allows user to save specific tasks under one of the 10 presets and call it back with shortcut
- RS232 Communication Control Input, allows to control switcher via included advanced Control software or Third Party Control System
- IR Remote Control
- Inputs: 8 x RGBHV female(5-BNC female per input)
- Outputs: 2 x RGBHV female (5-BNC female per output)
- Connectors: RGBHV (BNC style) (Could be used for PC resolutions up to UXGA 1600x1200 or HDTV up to 1080p)
- Compatible Formats: RGBHV, YPrPb, RGB, Composite
- · Lock Safe, allows user to lock unit from being accidentally switched to incorrect mode
- · Undo Function, allows user to undo the incorrect operation and return to the previous setting
- Standard 19&39;&39; Rack Mount Size 3U

## **Technical Specifications:**

- High Resolution Support: up to 1600x1200@85Hz or even higher
- Bandwidth: 450MHz @ (-3dB), fully loaded @1600x1200@85Hz or higher
- Cross talk sum: 56dB @10M; -40dB @100M
- Switching speed: 200 ns (Max)
- Signal type: RGB, YPrPb, RGBHV, RGBS, RGsB, RsGsBs, Component, Composite
- Standard 19&39;&39; Rack Mount Size -3U
- Connector: BNC female (5-BNC per input/output)
- Communication Port: RS232
- Impedance: 75 Ohm
- $\bullet\,$  Temperature: 20C to +70C (-20 F to 158 F )
- Power Supply: 110V-240V (50-60Hz)
- Dimensions (mm): W 485 X H 133 X D 266
- Dimensions (inch): W 19 X H 5.23 X D 10.47
- Unit Weight: 4.5kg or 9LBGross Package Weight: 13LB

# Package Includes:

- 1 x AT-RGB0802
- 1 x RS-232 Communication Cord
- 1 x Power Supply Cord (US)
- 1 x CD with RS232 Application Software
- 1 x IR Remote
- 1 x User&39;s Manual and Quality Guarantee

## **Warranty:**

2 year manufactures warranty (parts and labor)