

# Magenta Research 2211078-02 HDMI Video/Audio/IR/RS232 Extender (Receiver/Transmitter) Kit over Cat5e/6/6e/7

HD-One LX is an HDMI extension product that utilizes a single Cat5e/6/6e/7 cable, and sends 1080p video 328ft/100m. HD-One LX is fully HDCP-compliant and capable of extending uncompressed 1080p video, audio, IR and bi-directional RS-232 to 328ft/ 100m, allowing commands and data to flow in both directions.

The distance reach and use of inexpensive, easy to terminate UTP cable makes this product an obvious choice for HDMI extension, whether it's a Blu-Ray player, cable/set-top box or a PC with an HDMI/DVI output. Such distances are virtually impossible to replicate using specially constructed HDMI cables, which, even at short distances, deteriorate image quality, are extremely difficult to terminate in the field and carry a high cost factor. The HD-One LX delivers significant value and convenience for both commercial and residential applications.

Kit includes two sets of IR emitter/receiver cables.

## Key Features :

- HDMI 1.3 and HDCP compliant
- Uncompressed HD video to 1080p @ 60Hz at 328ft/100m
- Single UTP cable transfers video, audio, serial and HDCP signals
- Bi-directional RS232 interface
- Bi-directional IR functionality (two sets of emitter/receiver cables included)
- Audio transmission supports Dolby TrueHD, DTS-HD Master Audio

Connectors Required		
	Transmitter	Receiver
Video In	HDMI type A	
Video Out		HDMI type A
Audio In	Embedded with video signal	
Audio Out		Embedded with video signal
UTP In		RJ-45 (1)
UTP Out	RJ-45 (1)	
General Specifications		
Video Supported	HDMI/DVI Video Modes, including standard formats @ 60Hz:640x480, 800x600, 1024x768, 1152x864,1280x768, 1280x960, 1280x1024, 1360x760, 1366x768, 1600x1200,1680x1050, and HDTV: 480p,720p,1080i, and 1080p.	
Resolution	Up to 1080p / 60Hz / 48 bit / 3D Capable	
	Transmitter	Receiver
Audio Support	HDMI 1.3 audio: SPDIF two channel PCM or 5.1, 6,1 Dolby Digital or DTS)	
Cable Supported	High quality CAT5e, Cat6, CAT6e, CAT7, UTP / STP or FTP	
RS-232 Baud Rate	Up to 115200bps / Full Duplex	
RS-232 Connector	DB9 Female / DB9 Male	
IR Carrier	38Khz / 10o C / 5M / 2 Way	
Daisy Chain Capability	None	
Power	Regulated 5V / 2A	
Temperature Tolerance	Operating Temp: 0 to 55° C; Storage Temp: -20 to 85° C	
Humidity Tolerance	Up to 95% Non-Condensing	
Mounting	None	
Enclosure	Metal	
Size	4" x 3.25" x 1" (10.16 cm x 8.25 cm x 2.54 cm) each unit	
Weight	0.625 lb (0.283 kg) each	
Warranty	Three(3) Years	