# Atlona AT-VGA1601 Atlona 16x1 Professional VGA Switch

#### Atlona 16x1 Professional VGA Switch, Model: AT-VGA1601

The Atlona AT-VGA1601 is an 16 input 1 output Commercial VGA routing switcher. The AT-VGA1601 is one of the world&39;s advanced switchers. Is is capable of being cascaded, controlled though RS232 via software included or via a third party control system. Switcher is designed to handle any resolution up to UXGA (1600x1200) without any signal degradation.

This device is mainly used in broadcast room, multi council-chamber, television teaching room and command center.

#### **Main Features:**

- Power-Fail Protection, allows switcher to restore previous settings
- LCD display, shows all programmed commands and switcher responses
- Preset ability, allows user to save specific tasks under one of the 10 presets and call it back with shortcut
- RS232 Communication Control Input, allows to control switcher via included advanced Control software or Third Party Control System
- IR Remote Control
- Loop Connection, allows user to cascade up to 384 units (Example: 32x1, 48x1, 64x1 ets...)
- Inputs: 16 x VGA female15-pin HD
- Outputs: 1 x VGA female 15-pin HD
- Input: 1 x VGA female 15-pin HD (External Input Port if switcher is used in cascade mode)
- Connectors: 15-pin HD (Could be used for PC resolutions up to UXGA 1600x1200 or HDTV up to 1080p)
- Compatible Formats: RGB, YPrPb or RGBHV
- · Lock Safe, allows user to lock unit from being accidentally switched to incorrect mode
- · Undo Function, allows user to undo the incorrect operation and return to the previous setting
- Standard 19&39;&39; Rack Mount Size 2U

### **Technical Specifications:**

- High Resolution Support: up to 1600x1200@85Hz or even higher
- Bandwidth: 250MHz @ (-3dB), fully loaded @1600x1200@85Hz or higher
- Cross talk sum: 56dB @10M; -40dB @100M
- Switching speed: 200 ns (Max)
- Signal type: RGB, YPrPb, RGBHV, RGBS, RGsB, RsGsBs
- Standard 19&39; &39; Rack Mount Size 2U
- Temperature: 20C to +70C (-20 F to 158 F)
- Power Supply: 110V-240V (50-60Hz)
- Dimensions (mm): W 482.6 X H 87.2 X D 242
- Dimensions (inch): W 19 X H 3.42 X D 9.53
- Unit Weight: 4kg or 8LB
- Gross Package Weight: 12LB

## Package Includes:

- 1 x AT-VGA1601
- 1 x RS-232 Communication Cord
- 1 x Power Supply Cord (US)
- 1 x CD with RS232 Application Software
- 1 x IR Remote
- 1 x User&39;s Manual and Quality Guarantee

### Warranty:

2 year manufactures warranty (parts and labor)