

# Atlona AT-VGA0808-A 8x8 Professional VGA with Audio Matrix Switch

## Atlona 8x8 Professional VGA with Audio Matrix Switch. Model: AT-VGA0808-A

The Atlona AT-VGA0808-A is a 8 input 8 output Commercial VGA with Audio matrix switcher. The AT-VGA0808-A is one of the world's advanced matrix switchers. It is capable of being controlled through RS232 via software included or via a third party control system. Switcher is designed to handle any resolution up to UXGA (1600x1200) without any signal degradation. The switcher is capable of routing audio signals in a different matrix than video if applicable.

This device is mainly used in broadcast room, multi council-chamber, television teaching room and command center.

### Main Features:

- Power-Fail Protection, allows switcher to restore previous settings
- LCD display, shows all programmed commands and switcher responses
- Preset ability, allows user to save specific tasks under one of the 10 presets and call it back with shortcut
- RS232 Communication Control Input, allows to control switcher via included advanced Control software or Third Party Control System
- IR Remote Control
- Audio and Video could have a separate matrix modes (Example: Video in 1 ---> Video Out 2, while Audio in 1---> Audio Out 3)
- Inputs: 8 x VGA female 15-pin HD, 8 x screw audio terminals for balanced or unbalanced audio (Phoenix Connectors)
- Outputs: 8 x VGA female 15-pin HD, 8 x screw audio terminals for balanced or unbalanced audio (Phoenix Connectors)
- Connectors: 15-pin HD (Could be used for PC resolutions up to UXGA - 1600x1200 or HDTV up to 1080p)
- Compatible Formats: RGB, YPrPb or RGBHV
- Lock Safe, allows user to lock unit from being accidentally switched to incorrect mode
- Undo Function, allows user to undo the incorrect operation and return to the previous setting
- Standard 19" Rack Mount Size - 2U

### Technical Specifications:

- High Resolution Support: up to 1600x1200@85Hz or even higher
- Bandwidth: 250MHz @ (-3dB), fully loaded @1600x1200@85Hz or higher
- Cross talk sum: 60dB @10M; -39dB @100M
- Switching speed: 200 ns (Max)
- Signal type: RGB, YPrPb, RGBHV, RGBS, RGSB, RSGsBs
- Audio Connectors: screw audio terminals for balanced or unbalanced audio (Phoenix Connectors)
- Echo Loss: <-40dB@5MHz
- Audio Frequency: 20 Hz to 20 kHz,
- Standard 19" Rack Mount Size - 2U
- Temperature: 20C to +70C (-20 F to 158 F )
- Power Supply: 110V-240V (50-60Hz)
- Dimensions (mm): W 485 X H 90 X D 260
- Dimensions (inch): W 19 X H 3.54 X D 10.24
- Unit Weight: 3.5kg or 7LB
- Gross Package Weight: 10LB

### Package Includes:

- 1 x AT-VGA0808-A
- 1 x RS-232 Communication Cord
- 1 x Power Supply Cord (US)
- 1 x CD with RS232 Application Software
- 1 x IR Remote
- 16 x Phoenix Connectors for Audio
- 1 x User's Manual and Quality Guarantee

### Warranty:

2 year manufactures warranty (parts and labor)