

Atlona AT-COMP-13AD-b 1X3 COMPONENT VIDEO W/AUDIO DISTRIBUTION AMPLIFIER

Please **NOTE**: This listing is for **B-Stock** item. It means that this unit was refurbished by manufacturer and holds full manufacturer warranty, however it may have scratches, signs of wear and tear or come not in original box.

1x3 Atlona Component with Analog and Digital Audio Distribution Amplifier. Model: AT-COMP13AD

The 1x3 Component w/Audio Distribution Amplifier is the perfect solution for anyone who needs to send one source of high definition component video with Audio to multiple displays at the same time. It supports all component sources and displays. Supported resolutions: 480i, 480p, 576i, 576p, 720p, 1080i and 1080p. The AT-COMP13A is capable to send signal from one source to all 3 displays at the same time without signal degradation. The 1x3 Splitter will support long cable runs up to 100ft (30M).

Features:

- Accepts one component w/audio input and splits the input to 3 identical and buffered outputs
- Resolutions supported: 480i, 480p, 576i, 576p, 720p, 1080i and 1080p
- High bandwidth performance-480MHz bandwidth at-3dB
- Supports SD (composite, YCbCr) and HDTV (YPbPr, RGsB) input signal
- Plug and Play

Specifications:

- Video Input: YPbPr x1 or RGsB x1 (or RGBHV), or composite x3 1 Vp-p@ 75 ohm
- Video Output: YPbPr x3, or RGsB(or RGBHV) x3, or composite 3x3
- Audio input: Coaxial (S/PDIF) x 1 + R/L x 1
- Audio output: Coaxial (S/PDIF) x 3 + R/L x 3
- Analog audio input/output: Audio 2 Vrms max 47k ohm.
- Horizontal/Vertical sync 5Vp-p max and H frequency 10KHz~100KHz, V frequency 20Hz~200Hz.
- Video Bandwidth: 480MHz (-3dB)
- Video System: NTSC or Pal compatible
- Resolution: up to 1080p
- Differential gain: 0.05%
- Differential phase: 0.05 degree
- Power Supply: 5V 2A~1A
- Dimensions: 5.5"W x 1.5"H x 4.1"D
- Shipping Weight: 3Lbs.

Package includes:

- 1x3 Component w/audio Splitter
- One 6 foot Component cable
- 5V Universal Power Supply (110/220V)